




Function principle:

This biaxial inclination sensor uses 2 pieces of basic cells. The sensor works in the way that an electrolytical fluid is formed out by applying an AC-voltage on the planar electrode structures. By tilting the sensor, the fluid level over the different electrodes and in consequence the conductance of the stray field changes. Using a difference measurement principle, the tilt angle and the tilt direction can be measured. With a special electrode and circuit design the temperature coefficient is almost completely compensated.

Applications

- Zero point detection
- Laser leveling
- High end leveling
- Angle measurement

Pin out



Pining:

- | | |
|---|---------------------|
| 1 | Vcc + 5 VDC |
| 2 | Vref (out) + 2,5VDC |
| 3 | GND |
| 4 | V out X |
| 5 | V out Y |
| 6 | V out T |
| 7 | N.C. |
| 8 | N.C. |

Advantages

- Small size
- Easy to integrate
- Active temperature compensation
- Temperature output signal
- Low cost unit
- High linearity

Specification

	Conditions	Min	Typ	Max	Unit
Measurement range		-2	+2		°
Absolute maximum rating ⁽¹⁾		-10	+10		°
Sensitivity ⁽²⁾	RT ⁽²⁾	0.6	0.75	0.9	V/°
Offset	$V_{out\,x,y},\, RT^{(2)}$	$V_{ref}-0.5$	$V_{ref}+0.5$		V
Non linearity	up to +/- 1 °	-0.75	+0.75		% of FS ⁽³⁾
Non linearity	up to +/- 2 °	-1.5	+1.5		% of FS ⁽³⁾
Cross coupling angle	range end value	-0.03	+0.03		°
Output signal ^(4,5)	$V_{out\,x,y},\, V_{out\,T} \rightarrow GND$	0.3	$V_{cc}-0.3$		VDC
Temperature output signal	$V_{out\,T},\, 1.55V$ by 0 °C		30		mV/°C
Reference voltage output	V_{ref}	2.4	2.5	2.6	VDC
Power voltage supply	V_{cc}	4.75	5	5.25	VDC
Current consumption			15		mA
Operation temperature range		-10	+50		°C
Storage temperature range		-25	+85		°C
Weight			20		g
Dimensions	$W \times D \times H$	45	45	14	mm

¹⁾ by operating, under power supply.
Don't overstep the maximum rating.
Impairment of basic cells possible.
²⁾ RT = Room temperature 20°C
³⁾FS = Full Scale
⁴⁾measurement to Vref (bipolar)
or to GND (unipolar) possible.
⁵⁾by 10 kΩ load resistance

Compatible connector:
Company Molex
Picoflex PF-50 1,27mm (8 pins)

This inclinometer will be mount for horizontal position (x-y-plane) !