




## LUNEBERG REFLECTORS MONOSTATIC CIRCULAR POLARIZATION

<b>Plan #</b>	4LUN04R0007	
<b>R.C.S. Measurements</b>	We guarantee the specifications of the reflector according to plan # 4LUN04R0007. The reflector is delivered with 3 points of measurement ( $0^\circ$ / $-50^\circ$ / $+50^\circ$ in azimuth at $0^\circ$ of sight). The delivered measurement corresponds to the measurement of the lens alone. Further measurements options (patterns...) on specific request.	
<b>Response</b>	Monostatic	
<b>Polarization</b>	Circular. The radars use the circular polarization in particular in order to reduce the droplets effect. The circular radar reflector stands out of the clutter caused by the reflections of the rain because it reflects the signal without inversion of the direction of polarization, contrary to trihedral reflector or flat disk.	
<b>Metallization</b>	 label - metallization + - 0° +	Metallization on $\pm 70^\circ$ The label of metallization locates the plane of measurement at $\pm 50^\circ$ .
<b>Radom</b>	Waterproof composite protection (also against salted ambiance). Acceleration – vibration tests have been passed allowing mounting in supersonic targets	
<b>Standard fixing (in option)</b>	 plan 4LUN04D0005 Development of any other fixing at request	
<b>Specific unit packaging</b>		
<b>⚠ Precautions of use</b>	<p>The response of the lens depends on the environment.</p> <ul style="list-style-type: none"> <li>● Avoid thick fairing</li> <li>● Avoid fairing made of dielectrical material with important losses</li> <li>● Avoid any object (especially metallic) positioned between the lens and the radar (strap, screw...)</li> <li>● Take care in mounting</li> </ul>	  <p>OK radar</p> <p>Bad mounting radar</p>



**Tect Electronics**

*The authorized distributor in the Greater China Region*

SUNSTAR射频通信 <http://www.rfue.net/> TEL:0755-83397033 FAX:0755-83376182 E-MAIL: szss20@163.com

ISO 9001  
BUREAU VERITAS  
Certification

N° 1576 168





## LUNEBERG REFLECTORS MONOSTATIC CIRCULAR POLARIZATION

Reference	Frequency range	Measuring frequency (GHz)	Minimum Radar Cross Section guaranteed (sqm)		Diameter of the reflector without fixing		Weight without fixing (kg)
			R.C.S. in the axis	R.C.S. at $\pm$ azimuth angle	(inches)	(cm)	
XMC09	X	9,375	6	$\geq \pm 50^\circ$ 4	9,2	23	2,9
KMC07	Ku	15,54	6	$\geq \pm 50^\circ$ 5	7,0	18	1,3
KMC08.5	Ku	16,5	10	$\geq \pm 50^\circ$ 6	8,5	22	2,5
KMC09	Ku	16,5	11	$\geq \pm 50^\circ$ 7	9,2	23	2,9



*Tect Electronics*

*The authorized distributor in the Greater China Region*