



Product Specification of:

O₂ - Scuba Diving Sensor / Type D-05

:: KEY FEATURE ::

Galvanic gas sensor with an extra water repellent head space.

All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa.

Electrical Connector:	3-pin Molex [®] , gold-plated
Measurement Range:	0 to 100 Vol.%
Sensor Lifetime:	< 3 years @ ambient air
Expected Operating Life:	~ 500,000 Vol.% h
Intitial Output Signal:	9.0 to 12.0 mV @ dry ambient air
Response Time t₉₀:	< 5 s
Drift:	< 1 % volume O ₂ / month @ air, averaged across 12 months
Linearity Error:	< 3 % @ 100 % O ₂ , applied for 5 min
Zero Offset Voltage:	< 150 µV in 100% N ₂ , applied for 5 min
Operating Temperature:	0 to 45 °C
Pressure Range:	600 to 1750 hPa
Influence of Humidity:	-0.03% rel. O ₂ reading per % RH
Recommended Load Resistor:	≥ 10 kOhm
Temperature Compensation:	NTC
Interferences:	none to He, H ₂ and CO
Weight:	approximately 24 g
Material in Contact with Media:	PA, PPS, PTFE, stainless steel



:: STORAGE CONDITIONS ::

Temperature Range:	recommended: 5 to 30 °C maximum: -20 to 50 °C
Ambient Pressure:	600 to 1750 hPa
Humidity:	up to 100 % Rh
Shelf Life:	< 6 months recommended

:: RELATED PRODUCTS ::

Product	Part-No.	Housing Colour
O ₂ - Sensor D-05	41 00 55	white

This data sheet is subject to change without prior notice. [D-05-Rev_012011.doc]

page 1 of 1

IT Dr. Gambert GmbH :: Hinter dem Chor 21 :: 23966 Wismar :: Germany
Phone: +49 (0)3841 220 050 :: Fax: +49 (0)3841 220 052 2 :: E-Mail: sales@itg-wismar.de

www.itg-wismar.de